
# **PCM-23C1CF** PCM-23U1DG

#### 1 CFast Slot with Cover Protection

## **USB Slot w/ Lock for USB Dongle**



#### **Features**

- Meets Advantech Standard iDoor Technology
- Make device or system synchronization happen
- PCM-23C1CF supports single slot CFast II which will utilize the existing internal HDD cable
- PCM-23C1CF uses a captive screw type cover to protect the CFast
- PCM-23U1DG has locked type USB to prevent USB falling out
- Supports Embedded Automation Computers UNO-2200/2300/2400 series
- Supports Embedded DIN-Rail Controller UNO-1200/1300/1400 series
- Supports Embedded BOX IPC UNO-3000 series
- Supports Embedded Automation Panel Computers TPC-xx82/xx72/xx80 series







### Introduction

The PCM-23 series are storage modules from Advantech iDoor Technology. They are compatible with the PCI Express® Mini Card Specification Revision 1.2. including MRAM for automation machine memory back up which will no need battery, SATA to CFast on ThinClient terminal with storage for shorter maintenance and shorter MTB repair, Locked USB Dongle for Software protection in SCADA system, and TPM on Quality system management. This is a flexible design that enables customers to customize their features which meet iDoor Technology.

# **PCM-23C1CF Specifications**

#### General

Dimensions 19.4 x 81 x 41 mm I/O plate to SATA connector Features

Form Factor I/O Plate Contents I/O module, bracket • Operating Temperature  $0 \sim 60^{\circ}\text{C} (32 \sim 140^{\circ}\text{F})$ I/O Port CFast Type II connector

Quantity Color Silver

# **PCM-23U1DG Specifications**

#### General

Dimensions 19.4 x 81 x 41 mm (USB: L x W x H-max: 52 x 17 x 10) USB A type and 2.54 mm 5P header w/+5V supported Features

 Form Factor I/O Plate

Contents I/O module, cable, bracket • Operating Temperature  $0 \sim 60^{\circ}\text{C} (32 \sim 140^{\circ}\text{F})$ I/O Port Internal USB 2.0 Quantity

Color Silver

\* PCM-23U1DG must be utilized on the platforms which includes internal USB pin-header

# **Ordering Information**

PCM-23C1CF-AE SATAII 3G/Sec to CFast

# **Ordering Information**

PCM-23U1DG-AE USB Slot w/ Lock for USB Dongle